

# EasyPipe

## Shorter Installation Time and Reduced Costs

Webasto offers its customers pipes with pre-mounted insulation allowing significant savings concerning installation time on board. The special 13 mm insulation copes even with the most extreme air condition environments like tropical areas.

EasyPipe is made out of high-quality polybutylene resulting in perfect operation within a temperature range of -30°C up to 90°C at 6 bar. The pipe insulation is high-quality closed cell polyethylen with a temperature range of -30°C to 95°C and a lambda value of 0.0334 W/m K. Because of this high temperature tolerance, Webasto EasyPipe is suitable for air-conditioning as well as heating applications.

### Easy to fit:

The flexible pipe material can simply be cut to length and be combined with most common push-fittings to make a quick and reliable installation. The high-quality fittings can easily be re-opened if necessary and the smooth pipe interior provides less resistance to water flow than traditional tubing.



### Product Highlights:

- Pipe material is high-quality polybutylene
- Pipe insulation is high-quality closed cell polyethylen (PE-LD)
- O-ring sealed push fittings with stainless steel locking
- Sold in rolls to be cut to length
- Easy assembly process, reliable application
- Pipes have pre-mounted insulation that provides significant saving on installation time for boat builders
- Huge range of compatible quick-fitting components like Hep<sub>2</sub>O®
- Compatible to Hepworth Hep<sub>2</sub>O® connectors



For the complete Webasto range of accessories, please refer to the Marine catalogue.

**Three models for perfect applications:**

	<b>Diameter inside (mm)</b>	<b>Diameter outside (mm)</b>	<b>Length of roll (m)</b>
1	15	41	50
2	22	48	25
3	28	54	25

**Three different layers for perfect piping conditions:**

